



Open Ocean – Cape Coleville 240 Volt AC Modular – Data Sheet

This reverse osmosis desalination plant will utilize a commercial grade, high pressure pump, close coupled (no belts) to a 1.85kw, 240 Volt AC, electric motor. This supplies high pressure, pre-filtered sea water to a membrane array that produces a nominal 80 - 240 litres of potable water per hour from sea water at 25 degrees C and a salinity of 35,000 ppm, at an operating pressure of 800 – 850 psi.

The major components are assembled in **modular** form to best utilise your available space. These components are universal in nature and many of them are available worldwide, an important feature for a vessel operating internationally. Open Ocean keeps circuit boards, fancy controls and flashing lights off their products to provide the most **reliable** water maker possible.

Dimensions:

High pressure pump with electric motor 285mm wide X 560mm long X 255mm high

Membrane vessel 90mm wide x 1190mm long

Control Panel 430mm high X 380mm wide

Boost pump 240 V 290mm high X 390mm long X 195mm wide

Sea Water Filters 400mm high X 250mm wide X 130mm deep

Charcoal Flush Filter 400mm high X 300mm wide X 130mm deep



openocean@xtra.co.nz
www.openoceanwatermakers.co.nz

Options

Autoflush – automatically flushes fresh water through the system every 7 days, preserving the membranes. Especially good for boaters who don't get back to their boats as often as they mean to.



20 Micron Pre-filter

for systems that will operate in water with high levels of organics. Filters out plankton and silt before it gets to the 5 micron pre-filter extending its service life.

Specifications:

- 240 Volt AC electric motor
- 80 to 240 liters per hour @ approx 13 amps (one, two, or three membranes)
- Commercial quality reverse osmosis Stainless Steel high pressure pump
- Reverse osmosis membranes and 2000 psi fiberglass / carbon pressure vessel modules
- 240 Volt centrifugal sea water rated low pressure boost pump
- 5 micron polyester pleated **washable** pre-filter for cost effective long life filtration
- Fresh water flush facility: Charcoal filter connects to your onboard pressure water system to flush the water maker with fresh water
- Pressure relief valve – protects components from accidental over pressure situations
- Test, rejection and regulation valves
- High pressure hose / nylon non-corrosive tubing – can be cut and fit aboard
- All you need to provide is a sea strainer, access to the ship's water tanks, low pressure hoses, and any mounting benches or platforms required to position the Open Ocean components

Cape Coleville AC System Layout

